



Fibre-optic amplifier

OBF-FAKG/T/US

customer-specific

1 mounting on DIN rail
2 setting pushbuttons

Product characteristics

Type of light	red light
Housing	rectangular

Application

Special feature	Function check output
Design	Fibre-optic amplifiers for acrylic fibre optics

Electrical data

Operating voltage	[V]	10...30 DC
Current consumption	[mA]	< 50
Protection class		III
Reverse polarity protection		yes
Type of light		red light

Outputs

Electrical design		PNP/NPN; (automatic load detection PNP/NPN)
Output function		light-on/dark-on mode; (programmable)
Max. voltage drop switching output DC	[V]	2.5
Function check output		yes
Max. voltage drop of function check output	[V]	2.5
Permanent current rating of switching output DC	[mA]	100
Switching frequency DC	[Hz]	3000



Fibre-optic amplifier

OBF-FAKG/T/US

Short-circuit protection	yes	
Type of short-circuit protection	pulsed	
Detection zone		
Range [m]	0...2; (Through-beam sensor)	
Range [mm]	0...100; (Diffuse reflection sensor)	
Range adjustable	yes	
Operating conditions		
Ambient temperature [°C]	-25...60	
Protection	IP 65	
Tests / approvals		
EMC	EN 60947-5-2	
MTTF [years]	830	
Mechanical data		
Weight [g]	47.45	
Housing	rectangular	
Type of mounting	mounting on DIN rail; (TH35 (EN 60715))	
Dimensions [mm]	36 x 15 x 60	
Number of channels	1	
Materials	housing: PPE modified	
Displays / operating elements		
Display	switching status	1 x LED, yellow
	operation	1 x LED, green
	unsafe zone	1 x LED, red
	excess gain	4 x LED, green
Remarks		
Remarks	light-on mode corresponds to the NC output function for through-beam fibre optics	
	corresponds to the NO output function for diffuse-reflection fibre optics	
	dark-on mode corresponds to the NO output function for through-beam fibre optics	
	corresponds to the NC output function for diffuse-reflection fibre optics	
Notes	customer-specific	
Pack quantity	1 pcs.	

Electrical connection


Connector: 1 x M12; coding: A



Fibre-optic amplifier


OBF-FAKG/T/US

Connection



4 Function check output

Diagrams and graphs



x distance [mm]
y excess gain graph